DRIFTER DEPLOYMENT INSTRUCTIONS

Please Read Carefully

FOLD

1. Remove protective plastic wrap




2. <u>DO NOT REMOVE</u> paper tape or cardboard. ONLY remove plastic wrap.



3. Throw the buoy into the water.





DRIFTER DEPLOYMENT INSTRUCTIONS SVP AND SVP-BAROMETER DRIFTERS

- 1) Before deployment, remove **ONLY** the plastic shrink-wrap.
- 2) **DO NOT REMOVE** the paper tape securing the drogue and/or tether. Likewise, **DO NOT REMOVE** the cardboard surrounding the float.

WARNING: DO NOT REMOVE the paper tape securing the tether and drogue. If you do, the drogue and/or tether can unfurl during deployment and may cause injury!

- 3) Record the ID number listed on the drifter. This number can be found on the shipping container, the plastic shrink-wrap, or the protective cardboard box. It is also listed on the surface float itself.
- 4) Deploy the buoy from the stern, at lowest possible deck (preferably less than 10 meters, including heave), into the sea. The ship may be traveling between 1 and 20 knots. The tether and drogue are secured with paper tape that will dissolve in the water.
- 5) Record the date, time (GMT), coordinates at deployment, and deployment details, then email this information to the Global Drifter Program.

Thank you kindly for your assistance!

Log Sheei				
Ship Name:				
Drifter ID # xxxxxxxxxx	Date mm/dd/yyyy	Time (GMT)	Latitude DD mm.mm N/S	Longitude DDD mm.mm E/W
	//	::		
Deployed From	n: Starboard / Mid-Ship /	Port Stern	Ship Speed:kno Height Above Mean S	
	Port Side			
Mid-Ship Stern		3		
St	arboard Side			
_				

Submit deployment information to:

Shaun Dolk

Log Shoot

E-mail: drifter.deployment@noaa.gov

Web Submission: http://www.aoml.noaa.gov/phod/gdp/deployment submission form.php