MATURE STAGE EXPERIMENT Science Description

Experiment/Module: Research In Coordination with Operations Small Unmanned Aircraft Vehicle Experiment (RICO SUAVE)

Investigator(s): Joseph Cione, Jun Zhang, George Bryan (NCAR), Ron Dobosy (NOAA/ARLret), Altug Aksoy, Frank Marks, Kelly Ryan, Brittany Dahl, Josh Wadler, Josh Alland (NCAR), Rosimar Rios-Berrios (NCAR), Gijs deBoer (NOAA/PSL), Evan Kalina (NOAA/DTC), Don Lenschow (NCAR), Xiaomin Chen, Chris Rozoff (NCAR), Eric Hendricks (NCAR), Falko Judt (NCAR), Jonathan Vigh (NCAR)

Requirements: Category 1-5

Plain Language Description: This experiment uses small drones, instead of manned aircraft, to sample the lowest and most dangerous regions of the tropical cyclone. It is believed that observations from these unique platforms will improve basic understanding and enhance forecaster situational awareness. Detailed analyses of data collected from these small drones also have the potential to improve the physics of computer models that predict changes in storm intensity.

Mature Stage Science Objective(s) Addressed:

1) Test new (or improved) technologies with the potential to fill gaps, both spatially and temporally, in the existing suite of airborne measurements in mature hurricanes. These measurements include improved three-dimensional representation of the hurricane wind field, more spatially dense thermodynamic sampling of the boundary layer, and more accurate measurements of ocean surface winds [IFEX Goals 2, 3]

Motivation: Reducing the uncertainty associated with TC intensity forecasts remains a top priority of NWS/NHC. In addition to NOAA's operational requirements (sampling surface wind and thermodynamic structure), developing the capability to regularly fly low altitude unmanned aerial system (UAS) into TCs helps to advance NOAA research by allowing scientists to sample and analyze a region of the storm that would otherwise be impossible to observe in detail (due to the severe safety risks associated with manned reconnaissance). It is believed that such improvements in basic understanding are likely to improve future numerical forecasts of TC intensity change. Over time, projects such as this, which explore the utilization of unconventional and innovative technologies in order to more effectively sample critical regions of the storm environment should help reduce this inherent uncertainty.

Background: The Area-I Altius 600 is an electric-powered small Unmanned Aircraft System (sUAS) that has 3-5 h of endurance with up to a 150nmi range. It has a wingspan of 8 feet and a gross weight of 25lbs. Once airborne, the sUAS collects in-situ measurements of temperature, relative humidity, pressure, and remotely senses sea surface temperature (Zhang et al. 2016). The three-dimensional winds are also determined using information from the aircraft's autopilot. In some ways, the Altius 600 sUAS is similar to the GPS dropsonde since both observing platforms are air-deployed and both use identical (Vaisala RD41) meteorological payloads. However, unlike the dropsonde, the Altius 600 can target specific areas within the storm circulation in detail (both

MATURE STAGE EXPERIMENT Science Description

in the horizontal and in the vertical). Furthermore, observations from the Altius 600 are continuous and long duration (hours versus minutes) which gives scientists an extended look into important small-scale thermodynamic and kinematic turbulent processes that regularly occur within the near-surface TC boundary layer (Cione et al 2016, Cione et. al 2020). The Altius 600, when operated within a hurricane environment, provides a unique observation platform to observe the low-level atmospheric boundary layer and sea surface environment in great detail.

Goal(s): This module aims to collect PTHU observations within the high wind eyewall and boundary layer inflow regions of mature hurricanes. A primary goal is to provide real-time data of winds to improve operational situation awareness (RMW, VMax). An equally important, albeit longer-term goal, is to improve basic understanding of a sparsely-sampled, yet critically important region of the storm where turbulent exchanges of heat, moisture, and momentum with the ocean and eye-eyewall interfaces regularly occur. These observational data will also be used to evaluate operational model performance as it relates to boundary layer thermodynamic and kinematic structure and SST ocean response.

Hypotheses:

- 1. 360-degree depictions of hurricane boundary layer RMW and Vmax at multiple altitudes are possible by conducting UAS eyewall orbit missions by strategically synchronizing the prevailing wind direction with UAS heading.
- 2. Accurate depictions of the TC thermodynamic and kinematic inflow layer (100-1500m) are possible using dropsonde and sUAS strategically deployed observations.
- 3. Eye loitering, TC center fixes and eye-eyewall targeting sampling are possible using sUAS.

Objectives:

- 1. Eyewall module: Make sUAS HDOBS are made available in near-real-time to NHC; Report estimates of RMW and Vmax at multiple altitudes and azimuths to NHC in near real time. In post storm mode, conduct analyses comparing sUAS atmospheric and SST high wind eyewall observations with operational analysis and forecast fields from HWRF and HAFS.
- 2. Inflow module: Make sUAS HDOBS are made available in near-real-time to NHC and EMC. In post storm mode, compare sUAS TC boundary layer thermodynamic and kinematic radial structure (including SST) with numerical equivalents to improve TC boundary layer parameterizations and ocean response in HWRF and HAFS.
- 3. Center fix/Eye-Eyewall module: Make sUAS HDOBS are made available in near-realtime to NHC and EMC. Report center fix estimates to NHC in near-real time. In post storm mode, compare sUAS TC boundary layer thermodynamic and kinematic and SST structure within the eye and eye/eyewall interface with numerical equivalents to improve TC boundary layer parameterizations and ocean response in HWRF and HAFS.

MATURE STAGE EXPERIMENT Science Description

P3 and sUAS Aircraft Pattern/Module Descriptions (see *Flight Pattern* document for more detailed information):

P-3 Pattern #1: sUAS Eyewall Circumnavigation

This P-3 module can be conducted using any pattern that maximizes azimuthal eyewall coverage and will collect flight level, TDR, dropsonde, AXBT and SFMR observations for sUAS comparison and validation. The P-3 pattern should maximize eyewall sampling and penetration count. Dropsondes, SST-capable dropsondes, and AXBTS (10-15 total) will be deployed in locations that are collocated with sUAS underflights.

P-3 Pattern #2: sUAS Inflow

This P-3 module will be conducted preferably using a standard lawnmower pattern whereby the P-3 flies orthogonal to the sUAS inflow trajectory. The P-3 will collect flight level, TDR, dropsonde, AXBT and SFMR observations for sUAS comparison and validation. Dropsondes, SST-capable dropsondes, and AXBTS (10-15 total) will be deployed in locations that are collocated with sUAS underflights.

P-3 Pattern #3: sUAS Center Fix/Eye Loiter/Eye-Eyewall Sampling Module

This P-3 module can be conducted using any pattern that maximizes inner core coverage and will collect flight level, TDR, dropsonde, AXBT and SFMR observations for sUAS comparison and validation. Dropsondes, SST-capable dropsondes, and AXBTS (10-15 total) will be deployed in locations that are collocated with sUAS underflights.

Links to Other Mature Stage Experiments/Modules: The RICO SUAVE Experiment can be flown in conjunction with following *Mature Stage* experiments and modules: Eye-Eyewall Mixing, Gravity Wave, Convective Burst Structure and Evolution, Rainband Complex Survey, Surface Wind Speed and Significant Wave Height Validation, TC Diurnal Cycle, Synoptic Flow, NESDIS JPSS Satellite Validation, ADM-Aeolus Satellite Validation, and NESDIS Ocean Winds.

Analysis Strategy: The analysis of these data includes two components: understanding hurricane boundary layer structure and potential improvements to hurricane prediction that sUAS observations can provide. Existing working groups are currently analyzing sUAS data and are focused on two main areas: boundary layer turbulence and thermodynamics and observing system experiments. Data from these sUAS missions can resolve small scale features and physical processes that can then be compared and contrasted with similar boundary layer representations from multiple numerical models (HWRF, HAFS, CM1). In addition, research involving observing system experiments (OSEs) and observing system simulation experiments (OSEs) will be used to help quantify the impact of Coyote observations and allow help optimize Coyote resources by comparing observing strategies generated from a Nature Run.

References:

Cione, J.J., G. Bryan, R. Dobosy, J. Zhang, G. de Boer, A. Aksoy, J. Wadler, E. Kalina, B. Dahl, K. Ryan, J. Neuhaus, E. Dumas, F. Marks, A. Farber, T. Hock and X. Chen 2020: Eye of

MATURE STAGE EXPERIMENT Science Description

the Storm: Observing Hurricanes with a Small Unmanned Aircraft System. *Bull. Amer. Meteor. Soc.* <u>https://doi.org/10.1175/BAMS-D-19-0169.1</u>

- Cione, J. J., E. Kalina, E. Uhlhorn, and A. Damiano 2016: Coyote Unmanned Aircraft System Observations in Hurricane Edouard (2014). Earth Space Sci., doi:10.1002/2016EA000187
- Zhang, J. A., J. Cione, E. Kalina, T. Hock, J. Smith 2016: Novel Measurements of Sea Surface temperatures in Tropical Cyclones Obtained from GPS Dropsonde; 32nd Conference on Hurricanes and Tropical Meteorology, 12-18 April 2016, San Juan, Puerto Rico.