

## INSTRUMENT DESCRIPTIONS

---

The following are descriptions of instruments being flown on the P-3 and the G-IV aircraft and ocean observing platforms and aircraft-deployed expendables planned for deployment before and during the 2022 Atlantic hurricane season include:

### **1. Flight-level Measurements [P-3s and G-IV]**

Data from flight-level measurements are provided at 40 Hz (FAST) and 1 Hz and include: positional information, true air and ground speed, radar and pressure altitude, static and dynamic air pressure, air temperature, dew point temperature, d-value, horizontal and vertical wind, water vapor mixing ratio, and extrapolated surface pressure.

### **2. Tail Doppler Radar (TDR) [P-3s and G-IV]**

The P-3 and G-IV tail Doppler radar (TDR) systems have two solid-state transceivers that simultaneously transmit through the fore and aft antennas. The antennas are canted approximately 20 degrees fore or aft of the plane normal to the fuselage of the aircraft. The pulse repetition frequency is about 3000 Hz, and a long compressed pulse is used to produce sensitivity on the order of -10 dBZ at 10 km. For the P-3 TDR, a short pulse is added to provide data in the first 3 km from the aircraft. The frequency of the radar is in the X-band, with a wavelength of approximately 3 cm, and the beam width is approximately 2 (2.7) degrees for the P-3 (G-IV).

### **3. Multi-Model Radar (MMR) [P-3s]**

The Multi-Mode Radar (MMR) is an X-band, horizontally-scanning pulse Doppler radar system with a range up to 200 n mi, that has multiple operational modes available to the radar operator. Most relevant to hurricane operations is the Hurricane Weather mode (HWX) with turbulence identification. HWX mode shows nine colors referenced to reflectivity (dBZ) on the aircraft display, with the ninth color (white) being designated for turbulence detection when the range is set to less than or equal to 40 n mi. The pulse repetition frequency is about 1000 Hz, but varies according to maximum recording range, and the horizontal and vertical beam widths are 1.4 and 5 degrees, respectively.

### **4. Stepped Frequency Microwave Radiometer (SFMR) [P-3s and G-IV]**

SFMR is an airborne microwave radiometer that offers retrieved surface wind speed and rain rate by measuring the surface brightness temperature at nadir at six C-band frequencies between 4.7 and 7.1 GHz. The apparent brightness temperature of the ocean surface is sensitive to the sea surface temperature (SST) and surface foam coverage due to wave breaking; as the surface wind speed increases, so does the coverage of sea foam and, subsequently, the brightness temperature (Nordberg et al. 1971; Rosenkranz and Staelin 1972; Klotz and Uhlhorn 2014). Therefore, brightness temperature increases with surface wind speed for a given SST. A retrieval algorithm uses the relationship between the surface emissivity and wind speed, as well as the relationship between rain emissivity and frequency (using a geophysical model function, GMF, and inversion algorithm) to retrieve surface wind and rain rate estimates along the flight track (Uhlhorn et al. 2007). Klotz and Uhlhorn (2014) corrected a deficiency in the SFMR surface wind speed algorithm for an overestimation of wind speed in weak wind and heavy rain conditions by revising the GMF

## INSTRUMENT DESCRIPTIONS

---

coefficients for both the rain absorption and wind-induced surface emissivity models. The result was a significantly reduced bias at wind speeds less than hurricane force, and more accurate retrieved rain rates.

This season, dedicated SFMR experiment objectives are to:

1. Collect collocated SFMR and dropsonde data in high wind regions (surface wind speeds  $\geq$  100 kts).
2. Collect off-nadir SFMR observations at several different incidence angles in several different storm-relative locations.
3. Collect SFMR, flight-level, dropsondes, and TDR data over buoys.
4. Collect SFMR, dropsonde, flight-level, WSRA (when available), IWRAP (when available), and/or DWL (when available) coincident with SAR data acquisition.

### 5. GPS Dropsondes [P-3s and G-IV] and Ocean Profilers [P-3s]

The GPS dropwindsonde (dropsonde) is part of the National Center for Atmospheric Research (NCAR) / Earth Observing Laboratory (EOL) AVAPS (Airborne Vertical Atmospheric Profiling System) Dropsonde system that measures vertical profiles of atmospheric temperature, pressure, humidity, and wind speed as it falls from the aircraft to the surface.

Ocean observing platforms and aircraft-deployed expendables planned for deployment before and during the 2022 Atlantic hurricane season include:

1. AXBTs (Airborne Expendable BathyThermograph): measure ocean temperature from the surface to depths of 400 m (shallow water probes) and 800 m (deep water probes)
2. AXCPs (Airborne Expendable Current Profilers): measure ocean temperature and velocity versus depth
3. AXCTDs (Airborne Expendable Conductivity, Temperature, and Depth probes): measure ocean temperature and salinity versus depth
4. NOAA Hurricane Underwater Glider (autonomous underwater vehicle): profiles of temperature, salinity, and density structure from the near ocean surface to 1000 m
5. Saildrone (uncrewed surface vehicle): sea surface temperature and salinity, upper ocean (6-100 m) currents with 2 m resolution, surface air temperature & humidity (2 m), pressure (0.5 m), and wind direction & wind speed (3.2 m), wave height & wave period.
6. Surface drifting buoys [SVPB (<https://gdp.ucsd.edu/ldl/svpb/>) and DWSB (<https://gdp.ucsd.edu/ldl/dwsbd/>)]: measure sea surface temperature, pressure, directional wave spectra

### 6. Cloud Microphysics [P-3]

The P-3s are equipped with cloud microphysics probes that image cloud and precipitation particles and produce particle size distributions. The probes flown will include

1. Droplet Measurement Technologies, Inc. (DMT) ([www.dropletmeasurement.com](http://www.dropletmeasurement.com)) **Cloud Combination Probe (CCP)** for aerosol and cloud hydrometeor size distributions from 2

## INSTRUMENT DESCRIPTIONS

---

to 50  $\mu\text{m}$ , 2-D images and precipitation size distributions between 25 and 1550  $\mu\text{m}$ , liquid water content from 0.05 to 3  $\text{g m}^{-3}$ . The CCP includes 2 droplet instruments:

- a. **Cloud Droplet Probe (CDP)** for hydrometeor sizes between 3 - 50  $\mu\text{m}$ )
  - b. **Cloud Imaging Probe (CIP)** for hydrometeor sizes between 25  $\mu\text{m}$  - 1.6 mm, including the **CIP Grayscale (CIP GS)** particle imaging module
2. **Precipitation Imaging Probe (PIP)** for hydrometeor sizes between 100  $\mu\text{m}$  and 6.4 mm
  3. **Cloud and Aerosol Spectrometer (CAS)** for aerosol and cloud hydrometeor size between 0.5 and 50  $\mu\text{m}$ ). The CAS forward resolution is 0.63 - 50  $\mu\text{m}$ , while the backward resolution is 1.6 - 100  $\mu\text{m}$ .

### 7. Imaging Wind and Rain Airborne Profiler (IWRAP) [P-3]

IWRAP, which is also known as the Advanced Wind and Rain Airborne Profile (AWRAP), consists of two dual-polarized, dual-incidence angle radar profilers operating at Ku- and C-bands, and measures profiles of volume reflectivity and Doppler velocity of precipitation, as well as ocean surface backscatter. For more information regarding the use of IWRAP during this year's HFP, please refer to the following three NESDIS Ocean Winds Experiment documents in the Mature Stage Experiment: *Science Goals & Observational Applications*, *Science Description*, and *Flight Pattern Descriptions*.

### 8. Ka-band Interferometric Altimeter (KaIA) [P-3]

KaIA is a next generation centimetric radar altimeter that provides real-time observations of significant wave height (SWH) of the ocean surface. The instrument is nadir-looking and operates at Ka and Ku bands.

capability of retrieving mean squared slope (MSS), relative ocean height, and wind speed estimates at low wind speeds.

### 9. Wide Swath Radar Altimeter (WSRA) [P-3]

The WSRA (developed by ProSensing: <http://www.prosensing.com>) is an instrument that provides for measurements of sea surface topography and rain rate. The WSRA measures the sea surface topography by determining the range to the sea surface in 80 narrow beams spread over  $\pm 30^\circ$  in the cross-track direction (Walsh et al. 2014). Using measurements of sea surface topography and backscattered power, the WSRA offers real-time information on significant wave height, ocean directional wave spectra, the mean square slope of the ocean surface, and rain rate. The mean square slope (i.e., the sea surface small-scale roughness) responds to changes in wind speed and can be determined by the variation of the radar-backscattered power with incidence angle. Data collected are transmitted to NHC for operational use. This season, the dedicated WSRA experiment goal is to collect WSRA data in the TC environment to help improve NHC/TAFB's High Seas analyses and forecasts and NOAA's Wavewatch III ocean model.

### 10. Compact rotational Raman Lidar (CRL) [P-3]

## INSTRUMENT DESCRIPTIONS

---

The CRL is powered by a Nd:YAG laser with 50 mJ pulse energy running at 30 Hz. The normal ocular hazard distance of CRL is less than 200 m, which allows eye-safe operation during aircraft normal operation away from airport. It uses a compact, lightweight transmitting-receiving system, which can be easily mounted to the P-3 nadir port. The CRL was initially developed to obtain 2-D distributions of water vapor, aerosols, and clouds and was first deployed on the University of Wyoming King Air (UWKA) in 2010 (Liu et al. 2014). The successful demonstration of CRL led to the development of MARLi. In early 2015, low-J and high-J pure rotational Raman channels (J is the rotational quantum number) were added to provide temperature measurements (Wu et al. 2016).

Although the 50-mJ laser limits water vapor measurements to short range under high solar background conditions, the CRL still can provide excellent data for characterizing the spatial variability of aerosol, water vapor, and temperature during night or under normal solar background conditions. CRL signals are sampled with an A/D card at 250 MHz, which corresponds to a 0.6 m vertical resolution. The temporal/horizontal resolution will be set depending on the application. The data acquisition system is capable of saving individual profiles, which correspond to about 3.6 m horizontal resolution at a typical P-3 cruise speed of 108 m s<sup>-1</sup>. The highest resolution data is important for studying ocean surface wave characteristics, fine-scale sea spray structure, and ABL height variation. Different post-averaging can be done to improve signal-to-noise ratio as necessary for different atmospheric features. CRL will collect data continuously during P-3 research and operational missions to provide real-time fine-scale environment variations in TC, which are hard to detect with satellite measurements or airborne passive sensors alone. With the current small laser, we expect CRL water vapor and temperature measurements to be limited within 2 km below aircraft altitude without extensive spatial averaging. The instrument can obtain surface aerosol measurements and surface wave structure when the P-3 flies within 3-4 km altitude and is clear of clouds. Such measurements are still valuable to characterize thermodynamics structure and aerosol variations within TC. For example, flights between the eyewall and rainbands can measure the inflow structure within the inner core. CRL also provides aerosol depolarization measurements, which can be used to effectively identify dust aerosols associated with the Saharan Air Layer (SAL).

### **11. Terrestrial High-energy Observations of Radiation (THOR) [G-IV]**

THOR is an array of scintillation detectors sensitive to high-energy radiation, including gamma-rays, neutrons, electrons, and positrons. These forms of radiation are produced in thunderstorms when high electric fields accelerate electrons to relativistic energies; collisions of these electrons with air molecules produce other high-energy particles and leave behind radioactive nuclei that produce further high-energy particles when they decay. The most dramatic high-energy events in thunderstorms are terrestrial gamma-ray flashes (TGFs), extraordinarily bright flashes of radiation visible from space and associated with roughly 1 out of 1000 lightning flashes. Lightning also produces much fainter bursts of x-rays associated with stepping leaders, and thunderclouds occasionally show more persistent "glows" of electron/gamma radiation which provide a second path (besides lightning) for charged clouds to discharge themselves. In order to be able to study events ranging from overwhelmingly bright to barely brighter than the radiation background due

## INSTRUMENT DESCRIPTIONS

---

to cosmic rays, THOR contains very large and very small plastic scintillators, such that events bright enough to paralyze the large detectors are detected without difficulty in the smaller ones. One sodium iodide scintillator provides higher-quality spectroscopy of gamma rays from radioactive decay.

### References

- Klotz, B.W., and E.W. Uhlhorn, 2014: Improved Stepped Frequency Microwave Radiometer Tropical Cyclone Surface Winds in Heavy Precipitation. *J. Atmos. Oceanic Technol.*, **31**, 2392–2408.
- Liu B., et al. 2014: Compact airborne Raman lidar for profiling aerosol, water vapor and clouds, *Opt. Express*, **22** (17), 20613–20621.
- Nordberg, W. J., J. Conway, D. B. Ross, and T. Wilheit, 1971: Measurements of microwave emission from a foam-covered, wind-driven sea. *J. Atmos. Sci.*, **28**, 429–435.
- Rosenkranz, P. W., and D. H. Staelin, 1972: Microwave emissivity of ocean foam and its effect on nadrial radiometric measurements. *J. Geophys. Res.*, **77**, 6528–6538.
- Uhlhorn, E. W., P. G. Black, J. L. Franklin, M. Goodberlet, J. Carswell, and A. S. Goldstein, 2007: Hurricane Surface Wind Speed Measurements from an Operational Stepped Frequency Microwave Radiometer, *Mon. Wea. Rev.*, **135**, 3070–3085.
- Walsh, E. J., I. PopStefanija, S. Y. Matrosov, E. Uhlhorn, and B. Klotz, 2014: Airborne Rain-rate Measurement with a Wide-Swath Radar Altimeter. *J. Atmos. Oceanic Tech.*, **31**, 860–875.
- Wu, D., et al., 2016: Airborne compact rotational Raman lidar for temperature measurement, *Opt. Express*, **24**, A1210–A1223.