

**MATURE STAGE EXPERIMENT**  
*Flight Pattern Description*

---

**Experiment/Module:** Surface Wind and Wave Validation Module

**Investigator(s):** Heather Holbach, Mark Bourassa (FSU), and Ivan PopStefanija (ProSensing Inc.)

**Requirements:** Categories 2–5

**Mature Stage Science Objective(s) Addressed:**

- 3) Test new (or improved) technologies with the potential to fill gaps, both spatially and temporally, in the existing suite of airborne measurements in mature hurricanes. These measurements include improved three-dimensional representation of the hurricane wind field, more spatially dense thermodynamic sampling of the boundary layer, and more accurate measurements of ocean surface winds [*APHEX Goal 2*]

**P-3 Pattern #1 Dropsonde Overflights (One P-3)**

**What to Target:** Surface wind speeds  $\geq 100$  kts, most likely in the eyewall

**When to Target:** This module can be flown during any pass through the storm center.

**Pattern:** This module can be flown with any of the standard in-storm flight patterns. The module consists of flying inbound, releasing a dropsonde, or rapid sequence of 3 dropsondes, targeting the surface wind speed and/or rain rate maxima, entering the eye, and then flying outbound  $\sim 30\text{--}40^\circ$  azimuthally downwind of the inbound leg to overfly the splash location of the dropsonde. It may be necessary to adjust the azimuthal separation of the inbound and outbound legs to account for eye size, storm strength, and flight altitude. Another option is to wait for the dropsonde(s) to splash, determine the splash location(s), and overfly the exact splash location(s).

**Flight altitude:** 8–12 kft (radar altitude is preferred)

**Leg length or radii:** Any

**Estimated in-pattern flight duration:**  $\sim 10\text{--}15$  min. The time separation between releasing the dropsonde and the outbound pass over the estimated splash location should be as close as possible to the time it takes for the dropsonde(s) to fall to the surface ( $\sim 5\text{--}6$  min) or the time it takes to obtain the dropsonde(s) splash locations(s) ( $\sim 10\text{--}15$  min).

**Expendable distribution:** Release a dropsonde targeting the surface wind speed maximum on the inbound leg. If possible, release 3 dropsondes in rapid succession to increase the chances of observing the surface wind speed maximum and high rain rates with a dropsonde. An AXBT is not required, but could provide helpful SST data if available.

**Instrumentation Notes:** Use standard SFMR set-up. Important to maintain as straight and level of flight as possible. If available, the WSRA, KaIA, and/or IWRAP should be operating normally.

**MATURE STAGE EXPERIMENT**  
*Flight Pattern Description*

---

**P-3 Pattern #2: Dropsonde Overflights (Two P-3s)**

**What to Target:** Surface wind speeds  $\geq 100$  kts, most likely in the eyewall

**When to Target:** This module can be flown during any mission using both P-3s and during any pass through the storm center.

**Pattern:** This module can be flown with any of the standard in-storm flight patterns. The module consists of one P-3 (preferably the P-3 with the WSRA) flying inbound and releasing a dropsonde targeting the surface wind speed maximum or a sequence of 3 dropsondes released in rapid succession to increase the odds of observing the surface wind speed and/or rain rate maxima. The second P-3 (preferably the P-3 with IWRAP) will fly inbound  $\sim 30\text{--}40^\circ$  azimuthally downwind of the first P-3 and approximately 5-6 min later (or the closest temporal spacing possible for safe operations) to overfly the splash location of the dropsonde(s). The two aircraft can be at different altitudes. It may be necessary to adjust the azimuthal separation of the two P-3s to account for eye size, storm strength, and flight altitude or to identify the actual splash location of the dropsonde(s).

**Flight altitude:** 8–12 kft (radar altitude is preferred)

**Leg length or radii:** Any

**Estimated in-pattern flight duration:**  $\sim 10\text{--}15$  min. The time separation between the two P-3s should be as close as possible to the time it takes for the dropsonde to fall to the surface ( $\sim 5\text{--}6$  min) or the time it takes to obtain the dropsonde(s) splash locations(s) ( $\sim 10\text{--}15$  min) while maintaining safety of flight.

**Expendable distribution:** The first P-3 will release a dropsonde targeting the surface wind speed maximum on the inbound leg. If possible, release 3 dropsondes in rapid succession to increase the chances of observing the surface wind speed maximum and high rain rates with a dropsonde. An AXBT is not required, but could provide helpful SST data if available.

**Instrumentation Notes:** Use standard SFMR set-up. Important to maintain as straight and level of flight as possible. If available, the WSRA, KaIA, and/or IWRAP should be operating normally.

**P-3 Pattern #3: Wind Buoy Overflights**

**What to Target:** Buoys within the storm environment that have a reliable anemometer.

**When to Target:** Any time during the flight when passing near or over a buoy.

**Pattern:** This module can be flown with any of the standard in-storm flight patterns. This pattern consists of flying a series of 10-minute legs, straight and level parallel to the flight-level wind direction in a region of homogenous wind and rain conditions upwind and downwind centered on the buoy's location for approximately 30 minutes.

**Flight altitude:** 8–12 kft (radar altitude is preferred)

**Leg length or radii:**  $\sim 70$  km

**MATURE STAGE EXPERIMENT**  
*Flight Pattern Description*

---

**Estimated in-pattern flight duration:** 30 min

**Expendable distribution:** Release a dropsonde during each pass over the buoy's location.

**Instrumentation Notes:** Use standard SFMR, flight-level, and TDR instrument set-ups. Important to maintain as straight and level of flight as possible.

**P-3 Pattern #4: High Seas**

**What to Target:** Regions with significant wave heights of 8 ft and greater.

**When to Target:** Begin data collection when approaching significant wave heights of 8 ft on first inbound pass and continue data collection when significant wave heights are  $\geq 8$  ft.

**Pattern:** This module can be flown with any of the standard in-storm flight patterns. This pattern consists of extending standard flight legs, when necessary, to obtain WSRA significant wave height measurements in all regions with significant wave heights  $\geq 8$  ft. PIs will advise LPS prior to and during flight on the extent of waves with significant wave heights  $\geq 8$  ft.

**Flight altitude:** 8–12 kft (10 kft is optimal and radar altitude is preferred)

**Leg length or radii:** Out to radius of significant wave heights  $\geq 8$  ft.

**Estimated in-pattern flight duration:** Data collection will occur during the entire flight. Extension of legs could add 30-60 min to a flight.

**Expendable distribution:** No expendables required.

**Instrumentation Notes:** Use standard WSRA set-up. Required to maintain 8-12 kft radar altitude for WSRA data collection.

**P-3 Pattern #5: Wave Buoy Overflights**

**What to Target:** Wave buoys within the storm environment.

**When to Target:** Any time during the flight when passing near (within 50 km) or over a wave buoy.

**Pattern:** This module can be flown with any of the standard in-storm flight patterns. This pattern consists of flying straight and level for 250 seconds (4 minutes and 10 seconds) on the approach to the buoy. If time allows, make a 90° turn (either direction) upon reaching the buoy and continue flying straight and level for an additional 250 seconds away from the buoy.

**Flight altitude:** 8–12 kft (10 kft is optimal and radar altitude is preferred)

**Leg length or radii:** ~60 km

## 2024 NOAA/AOML/HRD Hurricane Field Program - APHEX

### MATURE STAGE EXPERIMENT

#### *Flight Pattern Description*

---

**Estimated in-pattern flight duration:** Approximately 8.5 mins for the entire pattern with 90° turn at buoy. Important to maintain straight and level flight on inbound and outbound legs.

**Expendable distribution:** No expendables required.

**Instrumentation Notes:** Use standard WSRA set-up. Required to maintain 8-12 kft radar altitude for WSRA data collection. It is also desirable to overfly Saldrones or Sofar buoys when possible.