E.4 Boundary-Layer Scientist

The on-board boundary-layer scientist (BLS) is responsible for data collection from AXBTs, AXCPs, AXCTDs, BUOYs, and sea surface temperature radiometers (if these systems are used on the mission). Detailed calibration and instrument operation procedures are contained in the air-sea interaction (ASI) manual supplied to each operator. General supplementary procedures follow. (Check off and initial.)

E.4.1	Preflight
	 Determine the status of equipment and report results to the on-board lead project scientist (LPS).
	2. Confirm mission and pattern selection from the on-board LPS.
	3. Select the mode of operation for instruments after consultation with the HRD/BLS and the on-board LPS.
	4. Complete appropriate preflight check lists as specified in the ASI manual and as directed from the on-board LPS.
E.4.2	In-Flight
	 Operate the instruments as specified in the ASI manual and as directed by the on-boar LPS.
E.4.3	Post flight
	1. Complete summary check list forms and all other appropriate check list forms.
	2. Brief the on-board LPS on equipment status and turn in completed check lists to the LPS.
	3. Debrief as necessary at MGOC or the hotel during a deployment.
	4. Determine the status of future missions and notify MGOC as to where you can be contacted.

Form E-4 Page 2 of 3

AXBT and AXCP Check Sheet

Flight Number 030821 I	AXBT/AXCP Contract Number				
Take-Off Time	Landing Time				
Storm CBLAST TEST #2	Storm Direction/Speed				

1250mbl	
Seguence	1
2-1	1

AXCP/ AXBT #/Type	Channel Number	Lot Number	Drop Time (HHMMSS)	Deg.	Min.	Deg.	ng. Min	Surf Ter AXB	np.	MLD (m)	Comments
1/43	16		181509		37		-56	28.9			Cowb w/GPS
2/43	12		181764	26.	27	85.	60	28.5			Bronly
3/42	16							28.9			42 BT/Sono/GPS
4/42	12		183550	7				X	A I I		- Dud-
5/43	16		183804	25	18	86	14	29.0			Cowb w/GPS BT only 42 BT/Sono/GPS - Dud - BT only BT + GPS
6/43	12		184012	25	71	86	24	29.3			BT + GPS
		24/38	Leylon Co			110			N. TER	in Barr	CA CATTERN
		WHI THOU				Entint					
	FIFT I										
E-VERTICAL PROPERTY.											
		14.									
Sign											