Conductivity Calibration Report

Customer:	US Department of Commerce, NOAA		
Job Number:	71470	Date of Repo	ort: 10/26/2012
Model Number	SBE 04C	Serial Numb	oer: 042973
sensor drift. If the	calibration identifies a rk is completed. The 'd	ted 'as received', without cleaning or adju problem or indicates cell cleaning is nec as received' calibration is not performed i	cessary, then a second calibration is
conductivity. Users sensor condition du corrections for drift	must choose whether t cring deployment. In S	rovided, listing the coefficients used to co he 'as received' calibration or the previo SEASOFT enter the chosen coefficients. (consult the SEASOFT manual). Calibra nt data.	ous calibration better represents the The coefficient 'slope' allows small
'AS RECEIVED C	CALIBRATION'	✓ Per	rformed
Date: 10/26/2012	2	Drift since last cal:	-0.00030 PSU/monti
Comments:			
'CALIBRATION	AFTER CLEANING	G & REPLATINIZING' Per	rformed V Not Performed
Date:]	Drift since Last cal:	PSU/monti
Comments:			
*Measured at 3.0	S/m		

Cell cleaning and electrode replatinizing tend to 'reset' the conductivity sensor to its original condition. Lack of drift in post-cleaning-calibration indicates geometric stability of the cell and electrical stability of the sensor circuit.