



Sea-Bird Electronics, Inc.

13431 NE 20<sup>th</sup> Street, Bellevue, Washington, 98005 USA

Website: <http://www.seabird.com>

Phone: (425) 643-9866

Email: [seabird@seabird.com](mailto:seabird@seabird.com)

Fax: (425) 643-9954

## SBE 5T SUBMERISIBLE PUMP CONFIGURATION SHEET

Serial Number: **05-7890**  
Pressure Rating: **10,500m**  
Housing Type: **Titanium**

MRP PN: **05T.21130**  
Test Date: **10/17/2014**

### Pittman Motor Type

P/N 3711B112-R2, 3.55 ohms nominal (For applications up to 4500 RPM MAX)

3 Winding, standard voltage input (jump P5 to P6)

### Pump Specifications:

|                                                 |                |     |        |               |     |
|-------------------------------------------------|----------------|-----|--------|---------------|-----|
| Motor speed with $V_{IN}$ at 12.0V, no load:    | <b>3000.29</b> | RPM | TP1=   | <b>99.99</b>  | Hz  |
| Motor speed with $V_{IN}$ at 12.0V, 300mA load: | <b>2999.62</b> | RPM | TP1=   | <b>100.01</b> | Hz  |
| Motor Dropout Voltage:                          | <b>9.10</b>    | VDC | Speed= | <b>3000</b>   | RPM |
| Pump submerged, no load, $V_{IN}$ 12VDC:        | <b>100.00</b>  | mA  |        |               |     |