

SYSTEM CONFIGURATION

SBE 9plus CTD Underwater Unit	S/N 09-1335
Depth Capability	6800 meters
Pressure Sensor Range	10000 psia
Digiquartz Pressure Sensor (w/ temp-comp)	S/N 135375
Modulo 12P	S/N MOD12P-1356
AD590M (Pressure Temperature Coefficient)	0.01278873
AD590B (Pressure Temperature Coefficient)	-9.31412676
A/D Input Voltage Range	0 to 5 Volts DC
Temperature Sensor (SBE 3plus)	03-6243
Conductivity Sensor (SBE 4C)	04-4709
Pump (SBE 5T)	05-9256

SEASOFT CONFIGURATION:

The settings for the configuration of your instrument as delivered are documented below:

Configuration for the SBE 911plus/917plus CTD

Configuration file opened: 09-1335.xmlcon

Frequency channels suppressed Voltage words suppressed (1 word = 2 channels)

Deck unit or SEARAM

Computer interface

Scans to average

NMEA position data added NMEA depth data added
 NMEA device connected to deck unit NMEA time added
 NMEA device connected to PC

Surface PAR voltage added Scan time added

Channel	Sensor
1. Frequency	Temperature
2. Frequency	Conductivity
3. Frequency	Pressure, Digiquartz with TC