

SYSTEM CONFIGURATION

SBE 9plus CTD Underwater Unit	S/N 09P79223-1207
Depth Capability	6800 meters
Pressure Sensor Range	10000 psia
Digiquartz Pressure Sensor (w/ temp-comp)	S/N 131013
Modulo 12P	S/N MOD12P-1210
AD590M (Pressure Temperature Coefficient)	0.012796
AD590B (Pressure Temperature Coefficient)	-8.694466
A/D Input Voltage Range	0 to 5 Volts DC
Temperature Sensor (SBE 3plus)	03-5207
Conductivity Sensor (SBE 4C)	04-4346
Pump (SBE 5T)	05-7889
Temperature Sensor, Secondary (SBE 3plus)	03-5348
Conductivity Sensor, Secondary (SBE 4C)	04-4349
Pump, Secondary (SBE 5T)	05-7890

SEASOFT CONFIGURATION:

The settings for the configuration of your instrument as delivered are documented below:

Configuration file opened: 09-1207.xmlcon

Frequency channels suppressed Voltage words suppressed (1 word = 2 channels)

Deck unit or SEARAM

Computer interface

Scans to average

NMEA position data added NMEA depth data added
 NMEA device connected to deck unit NMEA time added
 NMEA device connected to PC

Surface PAR voltage added Scan time added

Channel	Sensor
1. Frequency	Temperature
2. Frequency	Conductivity
3. Frequency	Pressure, Digiquartz with TC
4. Frequency	Temperature, 2
5. Frequency	Conductivity, 2

New
Open...
Save
Save As...
Select...
Modify...
Report...
Help...
Exit
Cancel