HRD DROPWINDSONDE DATA ARCHIVE

High-resolution, operationally processed and raw dropwindsonde data, along with related transmitted messages and graphics, from both NOAA and United States Air Force 53rd Weather Research Squadron, are available as far back as 1996, although all types of files for each individual dropwindsonde may not be available. Dropwindsonde data from other agencies such as NASA and the Canadian government are also available. The data currently reside on HRD's public ftp/http server and are accessible by clicking on the respective links for each data type or via anonymous ftp by entering:

Web Clients: ftp://ftp.aoml.noaa.gov/hrd/pub/data/dropsonde

Terminal Clients: ftp ftp.aoml.noaa.gov user: anonymous

password: your e-mail adress cd hrd/pub/data/dropsonde

All dropwindsonde data files for each hurricane season are placed in a separate folder (directory) by agency and year, e.g., **HURR03** for **2003 NOAA** dropwindsondes, and then in one of five embedded folders, depending on the data type. Operationally processed data are located in the folder named "operproc.", transmitted messages are found in "transmit" and raw data in "raw". For most flights Skew-T log P diagrams and station graphics are also produced. When available these figures can be found in the "skewt" and "synmap" folders respectively. The data file names are based on a "Flight ID" consisting of the takeoff date (year, month, and day with respect to UTC), a letter indicating the aircraft: **H--N42RF (P-3)**, **I--N43RF (P-3)**, **N--N49RF (Gulfstream-IV)**, **A--USAF(C-130)**, **U--USAF(2021 and later)** and a sequence number following the plane indicator. Example: 20040914I1 is the flight ID for the first NOAA N43RF P-3 mission into Hurricane Ivan on 14 September 2004. Detailed information about the individual data formats follows.

Operproc:

Within the operproc folder are two types of files: catalog (CAT) and compressed and packed full-resolution data (FRD).

(1) Catalog Files (CAT)

These contain a text listing of all the dropwindsondes processed for a particular flight, including each dropwindsonde's unique serial number; the date, time, location, and aircraft pressure level at launch; and any pertinent comments, such as storm region. The naming convention of the files is **FlightID.cat**. Below is an example of the first few lines of a CAT file, **20180903H1.cat**

CATALOG OF I	PROCESSED	DROPWINDESONDES	FOR	20180903H1
--------------	-----------	-----------------	-----	------------

Seq	Serial #	Date/Time (UTC)	Lat (N)	Lon Pr		
1	163535005	180903 /221956	26.48	82.96	696.0 COMMENT	: Center, Good Drop; TDDryBiasCorrApplied
2	163835047	180903 /211611	25.98	84.00	504.7 COMMENT	: Point #3, Good Drop; TDDryBiasCorrApplied
3	163845013	180903 /212112	25.51	84.00	505.1 COMMENT	: Point #4, Good Drop; TDDryBiasCorrApplied
4	163845021	180903 /214234	25.46	81.96	505.6 COMMENT	: Point #7, Good Drop; TDDryBiasCorrApplied
5	164015068	180903 /211819	25.78	84.00	504.8 COMMENT	: Point #5, Good Drop; TDDryBiasCorrApplied
6	164015092	180903 /224025	27.77	83.81	695.6 COMMENT	: Endpoint, Good Drop; TDDryBiasCorrApplied
7	164015166	180903 /210504	26.98	84.00	547.5 COMMENT	: Point #2, Good Drop; TDDryBiasCorrApplied

(2) Full-Resolution Data Files (FRD)

These contain the operationally quality controlled 2-Hz(0.5-s) or 4-Hz (0.25-s) resolution observations in fixed-length, long **text** records for each individual dropwindsonde. All available full-resolution data files of dropwindsondes released during a particular flight are packed into a **Unix/Linux-tarball** and stored as **GNU-zip compressed files** named **FlightID_FRD.tar.gz**. Although manual and software-based quality control procedures were performed, the processing of these data

was performed on the aircraft, under time constraint and may occasionally contain erroneous data.

All the individual FRD files from the flight have the nomenclature of **gSondeID.frd**, in which the **d**ropwindsonde **ID** corresponds to a dropwindsonde's nine-digit serial number provided in the CAT file. From year 2018 onward the FRD files are named based on the time of launch, ie **D20210101000000.frd**.

Each FRD file consists of **two parts**:

(A) the **header** (20 lines) and (B) the **processed data records** (amount varies depending on drop altitude and rate of dronwindsonde descent).

(A) Header

The header comprises four sections: basic information, processing parameters, comments, and aircraft flight-level data.

- (1) Basic information. This contains the dropwindsonde serial number, date it was processed, date and time of launch, and aircraft from which it was deployed.
- (2) Sonde processing parameters. Information in this section includes:
 - any bias corrections applied to the dropwindsonde's pressure (mb), temperature (C), and relative humidity (%) observations
 - any pressure baseline correction (offset) introduced prior to the dropwindsonde's launch (mb)
 - the cutoff wavelengths of the low-pass time filter used to smooth the pressure, temperature, and humidity (PTH) and wind observations (s)
 - if dynamic temperature, dynamic relative humidity, or wind shear (WSHR) corrections have been applied
 - if an estimated pressure profile is used
 - the computed mean GPS vertical velocity error (m/s) -999.00 if missing
 - the height correction (WGACORR) assigned to the wind observations (m)
 - the anchor for the hydrostatic geopotential-height calculation--SFC surface (upward integration), FLT flight level (downward integration), MSG missing
 - the dropwindsonde splash pressure (mb) -999.0 if missing
 - the hydrostatically-determined surface pressure (mb) -999.0 if missing
 - any adjustment to the aircraft geopotential altitude applied when integrating heights downward (m)
- (3) Comment line. This is the same as the remarks in the CAT file for the corresponding sonde.
- (4) Aircraft flight-level data. The following information and flight-level measurements at launch are contained in this section (missing values are assigned -999.0): Date six-digit date of dropwindsonde launch (yymmdd) RH flight-level relative humidity (%)

Time six-digit time of dropwindsonde launch (hhmmss) PS flight-level pressure (mb)

SID Dropwindsonde ID, nine-digit serial number

GA flight-level geopotential altitude

Lat latitude of aircraft (degrees)

Lon longitude of aircraft (degrees)

WD flight-level wind direction (degrees)

WS flight-level wind speed (m/s)

TA flight-level temperature (C)

Navaid aircraft navigational aid systme (GP for GPS)

TD flight-level dew point temperature (C)

(B) Processed Data Records

The Fortran Equivalent Format for reading data records is

"(I4.4,2(2X,F6.1),3X,F7.2,3X,F6.1,2X,I6,2X,I4,2X,3(F7.2,3X),I3,2X,F6.1,2X,I6,5X,I1,3(3X,I1),4X,F8.3,2X,F8.3)"

After a column header line, the processed dropwindsonde observations are provided in sequential records. Each includes the following fields (missing values are assigned -999 or -999.0). The columns consist of the following:

- (1) IX four-digit record index number (last value is the total number of observation records)
- (2) t (s) elapsed time from launch
- (3) P (mb) pressure
- (4) T (C) temperature
- (5) RH (%) relative humidity
- (6) Z (m) geopotential height of the thermodynamic measurements (P, T, and RH)
- (7) WD wind direction in degrees
- (8) WS (m/s) wind speed
- (9) U (m/s) zonal (x-axis) component of wind
- (10) V (m/s) meridional (y-axis) component of wind
- (11) NS number of GPS satellites used in wind computation
- (12) WZ (m/s) vertical velocity (NOTE: this is only an estimate based on the dropwindsonde fall rate and theoretical fall rate so it is less accurate than the horzontal velocity values)
- (13) ZW (m) geopotential height of wind measurement (usually slightly different than Z)
- (14) FP pressure measurement quality flag
- (15) FT temperature measurement quality flag
- (16) FH relative humidity measurement quality flag
- (17) FW wind measurement quality flag
- (18) LAT (N) latitude (degrees north) of dopwindsonde location as determined by GPS
- (19) LON (E) longitude (degrees east) of dropwindsonde location as determined by GPS

The data flags, **FP**, **FT**, **FH**, **FW**, for pressure, temperature, humidity, and winds are respectively assigned one of the following numbers:

- 0 good data value
- 3 interpolated value
- 4 value is doubtful or of questionable accuracy
- 5 subjectively determined value
- 6 ten-meter value

Below is a sample partial listing extracted from a 20180903H1 flight FRD file, g164615116.frd. Lines 4-72 have been removed in order to only include valid data.

Time: 213521 Lon: 82.65 W TD: -9.3 C GA: 5824 m WS: 2.8 m/s SID: 164615116 RH: 68.0 % Navaid: GP																		
									_									
IX	t (s)	P (mb)	T (C)	RH (%)	Z (m)	WD	WS (m/s)	U (m/s)	V (m/s)	NS	WZ (m/s)	ZW (m)	FP	FT	FH	FW	LAT (N)	LON (E)
0001	0.0	-999.0	-999.00	-999.0	-999	-999	-999.00	-999.00	-999.00	8	-999.0	-999	0	0	0	0	25.499	-82.652
0002	0.3	-999.0	-999.00	-999.0	-999	-999	-999.00	-999.00	-999.00	8	-999.0	-999	0	0	0	0	-999.000	-999.000
0003	0.5	-999.0	-999.00	-999.0	-999	-999	-999.00	-999.00	-999.00	8	-999.0	-999	0	0	0	0	25.499	-82.652
0073	18.0	520.0	-2.84	-999.0	5558	248	1.72	1.60	0.63	11	-0.3	5558	0	0	0	0	25.499	-82.651
0074	18.3	-999.0	-999.00	-999.0	-999	247	1.71	1.58	0.67	11	-999.0	-999	0	0	0	0	-999.000	-999.000
0075	18.5	520.5	-2.85	-999.0	5552	245	1.71	1.55	0.71	11	-0.4	5552	0	0	0	0	25.499	-82.651
0076	18.8	-999.0	-999.00	-999.0	-999	244	1.70	1.53	0.75	11	-999.0	-999	0	0	0	0	-999.000	-999.000
0077	19.0	520.9	-2.86	-999.0	5545	242	1.70	1.51	0.79	11	-0.5	5545	0	0	0	0	25.499	-82.651

Transmit:

Within the transmit folder are **two** types of files: **HRD Spline Analysis** (**HSA**) and **Temp Drop** messages. These files contain the data which were processed in real time. The resolution of these data is somewhat limited, comprising manadatory levels (surface, 1000mb, 925mb, 850mb, 700mb, 500mb, 400mb, 300mb, 250mb, 150mb and 100mb) and significant levels (where there are local extrema of thermodynamic and/or wind data).

(1) Temp Drop (XMT)

A header line consisting of the unique dropwindsonde id and date and time of release is added to each of the Temp drop messages, which are then concatenated into a single file named "FlightID.xmt". Appendix G of the National Hurricane Operations Plan contains a full description of how to read the messages. An example of a single message from 20180903H1.xmt is given below.

```
Sonde # 164615106 2052 UTC 03 Sep 18
UZNT13 KWBC 032139
XXAA 53217 99280 70840 08184 99016 25219 06016 00143 25025 07019
92825 20409 09029 85552 16008 09531 70183 07822 09526 88999 77999
31313 09608 82052
61616 NOAA2 0207A GORDON
                              OB 99
62626 MBL WND 07522 AEV 33668 DLM WND 09026 016546 WL150 06518 08
0 REL 2797N08396W 205206 SPG 2797N08403W 205949 =
XXBB 53218 99280 70840 08184 00016 25219 11850 16008 22684 07028
33578 00704 44546 02724
21212 00016 06016 11950 08528 22850 09531 33652 10521 44586 07023
55546 09027
31313 09608 82052
61616 NOAA2 0207A GORDON
                              OB 99
62626 MBL WND 07522 AEV 33668 DLM WND 09026 016546 WL150 06518 08
0 REL 2797N08396W 205206 SPG 2797N08403W 205949 =
```

(2) HRD Spline Analysis (HSA)

These files consist of the Temp Drop messages, written out in column format and concatenated into a single file.

Fortran Equivalent Format for HSA files is "I2, X, F7.0, X, I4, X, F7.3, X, F8.3, X, 3(F.6.1, X), F7.1, 2(2X, F5.1), X, A4"

The data columns contain:

- (1) Sounding identifier, "1" for dropwindsonde
- (2) Date (YYmmdd)
- (3) UTC time (hhmm)
- (4) Latitude (degrees N)
- (5) Longitude (degrees W)
- (6) Pressure (hPa) (see WMO document for Pressure > 1050)

- (7) Temperature (C)
- (8) Relative humidity (%)
- (9) Geopotential height (m)
- (10) Zonal wind component
- (11) Meridional wind component
- (12) Level flag

A partial listing of **20180903H1.hsa** which corresponds to the Temp Drop message example above is given below. Missing data is assigned a value of -99.0.

```
1 180903. 2100 28.000 84.000 1099.0 -99.0 -99.0 781.0 -13.4 0.0 DLMW
1 180903. 2100 28.000 84.000 1070.0 25.2 88.7 1016.0 -7.1 -4.1 MANL
1 180903. 2100 28.000 84.000 1016.0 25.2 88.7 -99.0 -99.0 -99.0 SIGL
1 180903. 2100 28.000 84.000 1016.0 -99.0 -99.0 -99.0 -7.1 -4.1 SIGL
1 180903. 2100 28.000 84.000 1000.0 25.0 85.3 143.0 -9.2 -3.3 MANL
1 180903. 2100 28.000 84.000 950.0 -99.0 -99.0 -99.0 -14.3 -1.3 SIGL
1 180903. 2100 28.000 84.000 925.0 20.4 94.3 825.0 -14.9 0.0 MANL
1 180903. 2100 28.000 84.000 850.0 16.0 94.8 1552.0 -15.9 1.4 MANL
```

Skewt:

Skew-T, log-P diagrams for all the dropwindsondes processed from a particular flight in Portable Network Graphics (png) image format. Each sounding is plotted separately and depicts a sonde's vertical during its descent. The images are aggregated into a single compressed file named FlightID_SKEWT.tar.gz.

SynMap:

Plan view station (synoptic) maps in png image format at standard pressure levels are produced from the Temp Drop data for many of the flights. When available they are aggregated into a single compressed file named FlightID_SYNMAP.tar.gz.

Raw:

Airborne Vertical Atmospheric Profiling System (AVAPS) raw data from each mission are aggregated into a single compressed file named "FlightID_AVP.tar.gz" containing individual files with naming convention "gSondeID.avp". Often the same files with a date and time based naming convention are also available within "FlightID_DFILES.tar.gz. No quality control has been applied to these data and it is not suitable for scientific research without first processing with software such as The National Center for Environmental Research (NCAR) Atmospheric Sounding Processing Environment (ASPEN) program. The ASPEN software is freeware and can run on any Windows, Mac or Linux compatible computer platform. To download a copy of the latest version and obtain documentation, please visit the following website from the NCAR Atmospheric Technology Division (ATD). http://www.eol.ucar.edu/software/aspen

Each raw data file consists of 2 parts, (A) the 5 line header and (B) individual data records.

(A) Header

- basic information including unique dropwindsonde id and date and time of launch
- description of the data contained in the columns below
- continuation of description of the data contained in the columns below
- corresponding units for the data contained in the columns below
- line separating the header from the data
- (B) <u>Data Records</u> (missing data are indicated by values 99999.00, 9999.00, 999.00, 999.000000 or 99.00)

The data columns consist of:

- (1) AVAPS receiving channel
- (2) Data source indicator
- (3) Unique dropwindsonde id
- (4) UTC date (YYMMDD)
- (5) UTC time (hhmmss.ss)
- (6) Air Pressure (h-Pa)
- (7) Air Temperature (C)
- (8) Relative Humidity (%)
- (9) Wind Direction (Degrees with respect to North)
- (10) Horizontal Wind Speed (m/s)
- (11) Vertical Descent rate (m/s) calculated from using the theoretical fall rate and vertical displacement of the sonde (m/s)
- (12) GPS Longitude (Degrees E)
- (13) GPS Latitude (Degrees N)
- (14) Number of GPS Satellites used for wind retrieval
- (15) Individual Sensor Relative Humidity (%)
- (16) Individual Sensor Relative Humidity (%) not relevant for newer dropwindsondes
- (17) Total Number of GPS Satellites
- (18) Wind error estimated from AVAPS system (m/s)
- (19) GPS reported Geometric Altitude (m)

An example of raw data from **g163525040.avp** / **D20180910_162012.1** is given below.

Additional Data Formats:

Since 2019, dropsonde data in Binary Universal Form for the Representation of meteorological data (BUFR) format has been transmitted operationally from NOAA aircraft. These files contain one second resolution data from the FRD files. Information and support for the use of BUFR data can be accessed at: http://www.dtcenter.org/com-GSI/BUFR/index.php

Full resolution dropsonde data in self describing NETCDF format are available for most of the NOAA and USAF flights from 2019 onward

Data Usage:

If you download any of the on-line dropwindsonde data files, please acknowledge HRD when appropriate in manuscripts, presentations, documents, etc. describing results obtained from the sonde observations. This can be done by including text, such as:

GPS-dropwindsonde data are provided courtesy of the NOAA/AOML/Hurricane Research Division in Miami, FL (USA).

Also, it would be greatly appreciated if you could send a message to the <u>HRD dropwindsonde data manager</u> explaining how you plan to utilize the data. This will keep HRD abreast of your research efforts, allow suggestions for possible collaborations, and help avoid potential conflicts or duplication with other scientists, particularly those within HRD.

Any **questions** regarding this data archive may be directed to either:

Kathryn Sellwood, NOAA/AOML/HRD Sim Aberson, NOAA/AOML/HRD

email: Kathryn.Sellwood@noaa.gov Sim.Aberson@noaa.gov

Phone: 305-361-4320 or Phone: 305-361-4334

REFERENCES:

For a detailed description of GPS dropsondes and aircraft systems, please see:

- NCAR Atmospheric Technology Division
- NOAA Aircraft Operations Center
- Vaisala Corp.