

MATURE STAGE EXPERIMENT
Science Description

Experiment/Module: Research In Coordination with Operations Small Uncrewed Air Vehicle Experiment (RICO SUAVE)

Investigator(s): Joseph Cione, Jun Zhang, Josh Wadler (ERAU), George Bryan (NCAR), Ron Dobosy (NOAA/ARL-ret), Xiaomin Chen (UAH), Altug Aksoy, Sim Aberson, Frank Marks, Kelly Ryan, Brittany Dahl, Johna Rudzin-Schwing, (MS State), Josh Alland (NCAR), Rosimar Rios-Berrios (NCAR), Don Lenschow (NCAR), Chris Rozoff (NCAR), Eric Hendricks (NCAR), Falko Judt (NCAR), Jonathan Vigh (NCAR)

Requirements: Categories 2–5

Plain Language Description: This experiment uses small drones, instead of crewed aircraft, to sample the lowest and most dangerous regions of the tropical cyclone (TC). It is believed that observations from these unique platforms will improve basic understanding and enhance forecaster situational awareness. Detailed analyses of data collected from these small drones also have the potential to improve the physics of computer models that predict changes in storm intensity.

Mature Stage Science Objective(s) Addressed:

- 1) Test emerging (or improved) technologies with the potential to fill gaps, both spatially and temporally, in the existing suite of airborne measurements in mature hurricanes. These measurements include improved three-dimensional representation of the hurricane wind field, more spatially dense thermodynamic sampling of the boundary layer, and more accurate measurements of ocean surface winds and underlying oceanic conditions [*APHEX Goal 2*].
- 2) Collect observations targeted at better understanding internal processes contributing to mature hurricane structure and intensity change [*APHEX Goals 1, 3*].

Motivation: Reducing the uncertainty associated with TC intensity forecasts remains a top priority of NWS/NHC. In addition to NOAA’s operational requirements (sampling surface wind and thermodynamic structure), developing the capability to regularly fly low-altitude small uncrewed aircraft systems (sUAS) into TCs helps to advance NOAA research by allowing scientists to sample and analyze a region of the storm that would otherwise be impossible to observe in detail (due to the severe safety risks associated with crewed reconnaissance). It is believed that such improvements in basic understanding are likely to improve future numerical forecasts of TC intensity change. Over time, projects such as this, which explore the utilization of unconventional and innovative technologies in order to more effectively sample critical regions of the storm environment should help reduce this inherent uncertainty. Coordination with uncrewed ocean surface vehicles (saildrones) in a hurricane, if the opportunity arises, will enable for the first time collocated measurements of the upper ocean, air-sea interface, and atmospheric boundary layer from autonomous vehicles.

Background: The Area-I Altius 600 is an electric-powered sUAS that has 3-4 h of endurance with a maximum 190-n mi range (in clear air conditions). The aircraft has a wingspan of 8.3 ft and a

MATURE STAGE EXPERIMENT
Science Description

gross weight of 25-27 lbs. Once airborne, the sUAS collects in-situ measurements of pressure, temperature, relative humidity (PTHU), and remotely senses sea surface temperature. In 2023 the Altius will also have a new multi-hole pressure port probe capable of measuring turbulent wind quantities. In some ways, the Altius 600 sUAS is similar to the GPS dropwindsonde since both observing platforms are air-deployed and both use identical (Vaisala RD41) meteorological payloads. However, unlike the dropsonde, the Altius 600 can target specific areas within the storm circulation in detail (both in the horizontal and in the vertical). Furthermore, observations from the Altius 600 are continuous (~5 Hz) and long-duration (hours versus minutes) which gives scientists an extended look into important turbulence-scale thermodynamic and kinematic processes that regularly occur within the near-surface TC boundary layer (Cione et al. 2016, Cione et al. 2020). The Altius 600, when operated within a hurricane environment, will provide a unique observation platform to observe the low-level atmospheric boundary layer and sea surface environment in great detail.

It should also be noted that an additional sUAS (Black Swift Technologies S0) is also expected to be available during the 2023 HFP. The endurance for the S0 was recently tested to ~1.5h. Range tests are ongoing but the final values are expected to be similar to values observed using the Altius platform. This smaller drone (3 lbs, 3ft wingspan) will also measure pressure, temperature, and humidity (PTHU) and remotely sensed sea surface temperature. Wind velocity and atmospheric turbulence measurements will also be available using this aircraft.

Goal(s): This module aims to collect PTHU observations within the high-wind-speed eyewall and boundary-layer inflow regions of mature hurricanes. A primary goal is to provide real-time wind-velocity data to improve operational situational awareness (RMW, VMax). An equally important, albeit longer-term goal, is to improve basic understanding of a sparsely sampled, yet critically important region of the TC where turbulent exchanges of heat, moisture, and momentum with the ocean and eye-eyewall interfaces regularly occur. These observational data will also be used to evaluate model performance as it relates to boundary-layer thermodynamic and kinematic structure and ocean response.

Hypotheses:

1. 360-degree depictions of hurricane boundary-layer RMW and Vmax at multiple altitudes are possible by conducting UAS eyewall orbit missions by strategically synchronizing the prevailing wind direction with UAS heading.
2. Accurate depictions of the TC thermodynamic and kinematic inflow layer (100-1500 m) are possible using strategically deployed dropsonde and sUAS observations and can yield information about important physical processes that control TC intensity.
3. Deriving the vertical profile of turbulence information at hurricane-force wind speeds is feasible with the specifically-designed P-3 and sUAS flight patterns.
4. Eye loitering, TC center fixes, and eye-eyewall sampling are possible using sUAS.

MATURE STAGE EXPERIMENT
Science Description

Objectives:

1. Eyewall module: Make sUAS High Density Observations (HDOBs) available in near real-time to NHC; Report estimates of RMW and Vmax at multiple altitudes and azimuths to NHC in near real time. In post-storm mode, conduct analyses comparing sUAS atmospheric and SST eyewall observations with operational analyses and forecast fields from HWRF and HAFS. All sUAS data collected should be available in KARMA (AOC's P-3 situational awareness visualization tool).
2. Inflow module: Make sUAS HDOBS available in near real-time to NHC and EMC. In post-storm mode, compare sUAS boundary-layer thermodynamic and kinematic radial structure (including SST) with numerical equivalents to improve TC boundary layer parameterizations and ocean response in HWRF and HAFS. Also, use sUAS HDOBS to improve our understanding of the role of downdrafts in determining TC intensity as well as the turbulent structure of the boundary layer.
3. sUAS inflow-layer turbulence module: Make sUAS HDOBS available in near real-time to NHC and EMC. In post-storm mode, retrieve the vertical profile of eddy viscosity at hurricane-force wind speeds using the sUAS and dropsonde observations. This information is crucial for improving boundary-layer parameterizations used in NOAA's hurricane forecast models.
4. Center fix/Eye-Eyewall module: Make sUAS HDOBS available in near real time to NHC and EMC. Report center fix estimates to NHC in near-real time. In post-storm mode, compare sUAS-boundary layer thermodynamic and kinematic and SST structure within the eye and eye/eyewall interface with numerical equivalents to improve boundary-layer parameterizations and ocean response in HWRF and HAFS.

Aircraft Pattern/Module Descriptions (see *Flight Pattern* document for more detailed information):

P-3 Pattern #1: sUAS Eyewall Circumnavigation

This P-3 module can be conducted using any pattern that maximizes azimuthal eyewall coverage and will collect flight level, TDR, dropsonde, AXBT, and SFMR observations for sUAS comparison and validation. The P-3 pattern should maximize eyewall sampling and penetration count. Dropsondes, SST-capable dropsondes, and AXBTS (10-15 total) will be deployed in locations that are collocated with sUAS under flights.

P-3 Pattern #2: sUAS Inflow

With the ideal sUAS inflow module starting in the upshear-left quadrant, the ideal P-3 pattern starts with a radial penetration from the downshear-right to the upshear-left quadrant. After release of the sUAS, the P-3 flies a similar flight path as the sUAS, where dropsondes, SST-capable dropsondes, and AXBTS (10-15 total) will be deployed every 30 degrees in azimuth in locations that are collocated with sUAS under flights. The P-3 will then continue its standard flight pattern and collect flight level, TDR, CRL, dropsonde, AXBT, and SFMR observations for sUAS comparison and validation. This pattern is designed to study the effects of downdrafts on the

MATURE STAGE EXPERIMENT

Science Description

hurricane boundary layer which are persistent in the principal rainband in the left-of-shear quadrants (Riemer et al. 2010) whose effects have been recently shown to be height-dependent (Wadler et al. 2021). Flying the inflow module, mimics what the P-3 flew in Hurricane Bonnie (1998) and presented in Wroe and Barnes (2003).

P-3 Pattern #3: sUAS inflow-layer turbulence module

sUAS is released from P3 in hurricane conditions, typically within the core region of mature hurricanes. Prior to the beginning of the stepped descent mode of sUAS in the inflow layer, the ideal P3 flight pattern is “zig-zag” such that its radial penetration can be slowed down to keep up with the sUAS. A dropsonde is released from P-3 at the beginning of each flight leg, with a total of 7 dropsondes required. This pattern is designed to derive the vertical profile of eddy viscosity at hurricane-force wind speeds to fill in the gap of observations and to improve the PBL parameterizations in high-wind conditions (Chen et al. 2021; Chen 2022).

P-3 Pattern #4: sUAS Center Fix/Eye Loiter/Eye-Eyewall Sampling Module

This P-3 module can be conducted using any pattern that maximizes inner core coverage and will collect flight level, TDR, dropsonde, AXBT, and SFMR observations for sUAS comparison and validation. Dropsondes, SST-capable dropsondes, and AXBTS (10-15 total) will be deployed in locations that are collocated with sUAS under flights.

Links to Other Mature Stage Experiments/Modules: The RICO SUAVE Experiment can be flown in conjunction with following *Mature Stage* experiments and modules: Boundary Layer and Air-Sea Interactions, Eye-Eyewall Mixing, Gravity Wave, Convective Burst Structure and Evolution, Rainband Complex Survey, Surface Wind Speed, and Significant Wave Height Validation, TC Diurnal Cycle, Synoptic Flow, NESDIS JPSS Satellite Validation, ADM-Aeolus Satellite Validation, and NESDIS Ocean Winds.

Analysis Strategy: The analysis of these data includes two components: understanding hurricane boundary layer structure and potential improvements to hurricane prediction that sUAS observations can provide. Existing working groups are currently analyzing sUAS data and are focused on two main areas: boundary layer turbulence and thermodynamics, and observing system experiments (OSEs). Data from these sUAS missions can resolve small-scale features and physical processes that can then be compared and contrasted with similar boundary layer representations from multiple numerical models (HWRF, HAFS, CM1). In addition, research involving OSEs and observing system simulation experiments (OSSEs) will be used to help quantify the impact of sUAS observations and help optimize sUAS resources by comparing observing strategies generated from a Nature Run.

References:

Cione, J.J., G. Bryan, R. Dobosy, J. A. Zhang, G. de Boer, A. Aksoy, J. Wadler, E. Kalina, B. Dahl, K. Ryan, J. Neuhaus, E. Dumas, F. Marks, A. Farber, T. Hock and X. Chen 2020: Eye of the Storm: Observing Hurricanes with a Small Unmanned Aircraft System. *Bull. Amer. Meteor. Soc.* <https://doi.org/10.1175/BAMS-D-19-0169.1>

MATURE STAGE EXPERIMENT

Science Description

Chen, X., G. H. Bryan, J. A. Zhang, J. J. Cione, and F. D. Marks, 2021: A framework for simulating the tropical-cyclone boundary layer using large-eddy simulation and its use in evaluating PBL parameterizations. *J. Atmos. Sci.*, **78**, 3593-3611.

Chen, X., 2022: How do planetary boundary layer schemes perform in hurricane conditions: A comparison with large-eddy simulations. *J. Adv. Model. Earth Syst.*, **14**, e2022MS003088.

Cione, J. J., E. Kalina, E. Uhlhorn, and A. Damiano 2016: Coyote Unmanned Aircraft System Observations in Hurricane Edouard (2014). *Earth Space Sci.*, doi:10.1002/2016EA000187.

Riemer, M., M. T. Montgomery, and M. E. Nicholls, 2010: A new paradigm for intensity modification of tropical cyclones: Thermodynamic impact of vertical wind shear on the inflow layer. *Atmos. Chem. Phys.*, **10**, 3163–3188, <https://doi.org/10.5194/acp-10-3163-2010>.

Wadler, J. B., D. S. Nolan, J. A. Zhang, and L. K. Shay, 2021: Thermodynamic Characteristics of Downdrafts in Tropical Cyclones as Seen in Idealized Simulations of Different Intensities. *J. Atmos. Sci.*, **78**, 3503–3524, <https://doi.org/10.1175/JAS-D-21-0006.1>.

Wroe, D. R., and G. M. Barnes, 2003: Inflow Layer Energetics of Hurricane Bonnie (1998) near Landfall. *Mon. Wea. Rev.*, **131**, 1600–1612, <https://doi.org/10.1175//2547.1>.